

Fumebuster AC – Activated carbon welding fume extractor

AIR FILTRATION SOLUTIONS



- ✓ Accessories included, ideal for cleaning professionals.
- ✓ Compressed air supply via 2 Venturi units

Suction unit

Voltage	V - Hz	400 - 50 3~
Power	kW	1,5
Max air flow	m3/h	1300
Suction inlet	mm	150
Noise level (EN ISO 3744)	dB(A)	72

Filtering Unit

Cleaning system	Manual
Filtration efficiency	F9 95%

Collection unit

Capacity	lt	200
Liquid capacity	lt	50
Collection tank		Painted
Cyclon unit		Integrated
Discharge system		Disposable bag

Encumbrances

Dimensions	cm	65 x 75 x 129h
Weight	kg	131

APPLICATIONS:



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

Fumebuster AC – Activated carbon welding fume extractor

AIR FILTRATION SOLUTIONS

SUCTION UNIT

It is equipped with an electric fan that provides a high airflow, ideal for direct extraction of volatile chips generated by machine tool processes or suspended dust present in work environments.

FILTERING UNIT

The vacuum cleaner is equipped with a progressive filtration consisting of panel filters with 4 stages of filtration.

COLLECTION UNIT

Container made entirely of AISI 316 stainless steel

OPTIONALS

- ✓ Local remote start-up
- ✓ Local/remote control
- ✓ Stainless steel chamber