

Chipvac 200

INDUSTRIAL VACUUMS



- ✓ Possibility of turning upside down from 50° to 90° with the help of a forklift truck. Simple and effective DU-PUY patent system.
- ✓ Large capacity tilting vacuum cleaner for solids and liquids. Designed to make simplify the vacuuming of large quantities of different materials.

Suction Unit

Power supply	V - Hz	230 - 50 1~
Power	kW	3,3
Maximum depression	mmH2O	2.400 - 3.600
Maximum air flow rate	m3/h	540 - 340
Nozzle	mm	90
Noisiness (EN ISO 3744)	dB(A)	77-78

Filter Unit

Primary filter		Pockets
Surface area - diameter	cm ² -mm	14.000 - 420
Filter media - class	IEC 60335-2-69	Polyester L
Cleaning system		Handbook

Collection unit

Capacity	lt	200
Exhaust system		Tipping container

Encumbrances

Dimensions	cm	109x94x135h - 109x94x136h
Weight	kg	155 - 157

APPLICATIONS: Mechanical industry Glass



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

Chipvac 200

INDUSTRIAL VACUUMS

SUCTION UNIT

Suction is generated by three carbon brush by-pass motors activated by independent switches located on a solid metal head, soundproofed with sound-absorbing material.

FILTER UNIT

The polyester star filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuumed material is collected in the front discharge bucket, allowing the material to be disposed of quickly and without contamination. The vacuum cleaner is mounted on a sturdy powder coated steel frame, fitted with polyurethane wheels and designed for forklift intakes.

The container is compact and contains a sieve grid to separate the solids.

OPTIONALS

- ✓ Oil-proof seal
- ✓ Nomex filter - heat resistant up to 250°
- ✓ Antistatic filter class m
- ✓ Hydro-oleophobic filter class m
- ✓ Oil-chip separation grid