




- ✓ Extremely silent.
- ✓ Release container with the possibility of using disposable bags.
- ✓ Large capacity detachable container. Forklift intakes.
- ✓ Simultaneous vacuuming of dust, liquids and solids.
- ✓ Maintenance-free motor suitable for continuous operation.
- ✓ Integrated filter cleaning system

Suction Unit

Power supply	V - Hz	400 - 50 3~
Power	kW	4
Maximum depression	mmH2O	3.200
Continuous depression	mmH2O	2.700
Maximum air flow rate	m3/h	420
Limiting valve		Integrated
Nozzle	mm	80
Noisiness (EN ISO 3744)	dB(A)	74

Filter Unit

Primary filter		Pockets
Surface area - diameter	cm ² -mm	20.000 - 420
Filter media - class	IEC 60335-2-69	Polyester L
Cleaning system		Handbook

Collection unit

Capacity	lt	100
Collection system		Release container

Encumbrances

Dimensions	cm	119x65x160h
Weight	kg	137

APPLICATIONS:  Food, chemical and pharmaceutical industry  Mechanical industry  Glass  Sandblasting  Wood and plastic  General housekeeping

SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

FILTER UNIT

The filter can be cleaned by means of the integrated mechanical cleaning system: an external filter shaking lever shakes the filter with a vertical movement, ensuring an effective and safe cleaning action, maintaining constant suction power and preventing the dispersion of dust into the environment.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

OPTIONALS

- ✓ Hepa absolute filter /h14
- ✓ Stainless steel container
- ✓ Earthing
- ✓ Arrangement for endless bag
- ✓ Cyclone for filter protection
- ✓ Pressure relief valve
- ✓ Additional silencer
- ✓ Forklift intakes