MHD SERIES

INDUSTRIAL VACUUM CLEANERS

- Maintenance-free motor suitable for continuous operation.
- Extremely silent.
- Large capacity detachable container. Forklift intakes.

Suction Unit		
Power supply	V - Hz	400 - 50 3~
Power	kW	7,5 - 11 - 12,5 - 18,5
Maximum depression	mmH2O	4.500 - 4.000 - 4.400 - 4.400
Continuous depression	mmH2O	3.200 - 2.600 - 2.900 - 3.200
Maximum air flow rate	m3/h	750 - 1.050 - 1.100 - 1.350
Nozzle	mm	120
Noisiness (EN ISO 3744)	dB(A)	74 - 75 - 78 - 81
Filter Unit		
Primary filter		Pockets
Surface area - diameter	cm^2-mm	70.000 - 560
Filter media - class	IEC 60335-2-69	Polyester L
Collection unit		
Capacity	lt	160
Encumbrances		
Dimensions	cm	163x76x200h
Weight	kg	332 - 390 - 430 - 430

APPLICATIONS:

MHD SERIES

INDUSTRIAL VACUUM CLEANERS

FILTER UNIT

The polyester filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

OPTIONALS

- Alternative discharge systems
- Timed automatic filter shaker with compressed air cylinder
- Antistatic filter class m
- Ptfe-treated filter class m
- NOMEX heat-resistant filter up to 200°C
- Hepa absolute filter /h14
- Stainless steel container
- Stainless steel chamber
- Earthing
- Local remote start-up
- Bracket for lifting and tilting the container
- Abrasion proof plate in Hardox steel for filter chamber

All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it