

# Oilvac 200 T

## INDUSTRIAL VACUUMS



- ✓ Save money by recovering and reusing cutting oil and emulsion.
- ✓ Large grid basket to collect metal chips and oil microfiltration filters to remove dust and metal particles.
- ✓ Liquid level monitored by a floating device to stop when the container is full.

### Suction Unit

Power supply	V - Hz	400 - 50 3~
Power	kW	3
Maximum depression	mmH2O	3.200
Maximum air flow rate	m3/h	350
Nozzle	mm	50
Noisiness (EN ISO 3744)	dB(A)	76

### Filter Unit

Primary filter		Pockets
Surface area - diameter	cm <sup>2</sup> -mm	14.000
Filter media - class	IEC 60335-2-69	M ANT Hydro-oleo repellent

### Collection unit

Dust capacity	lt	30
Liquid capacity	lt	200
Float		Electric
Exhaust system		Immersion pump

### Encumbrances

Dimensions	cm	122x62x155h
Weight	kg	224

**APPLICATIONS:** Mechanical industry



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

# Oilvac 200 T

## INDUSTRIAL VACUUMS

### SUCTION UNIT

Three-phase model with 3kW side channel.

### FILTER UNIT

A float stops the suction when the liquid in the container reaches the maximum level, preventing spillage.

The polyester star filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

### COLLECTION UNIT

The vacuum cleaner is mounted on a sturdy metal frame and fitted with heavy-duty industrial wheels for easy manoeuvrability also on uneven surfaces.

A grid basket inside the container separates solids (chips, metal swarf) from liquids, which drain to the bottom of the container. The liquid is quickly disposed of via a manual liquid drain valve.

### OPTIONALS

✓ Recommended accessory Ø50