

# SPC MIST VERSION

## AIR FILTRATION SOLUTIONS



- ✓ Suitable for post-processing cleaning of parts from cooling lubricants and metal shavings.

### Suction Unit

Power supply	V - Hz	230 - 50 1~
Power	kW	0,75
Maximum air flow rate	m3/h	2.000
Nozzle	mm	100
Noisiness (EN ISO 3744)	dB(A)	65

### Filter Unit

Primary filter		Cartridge
Total filter surface area	cm <sup>2</sup>	100.000

### Collection unit

Dust capacity	lt	5
Exhaust system		Exhaust valve

### Encumbrances

Dimensions	cm	81x79x160h
Weight	kg	140

**APPLICATIONS:** Steel mills and foundries    Mechanical industry



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

# SPC MIST VERSION

AIR FILTRATION SOLUTIONS

## COLLECTION UNIT

The vacuumed material is collected in a stainless steel container, mounted on a tilting trolley.

Thanks to an discharge valve, the container can be emptied conveniently and quickly.