


WD 3000

INDUSTRIAL VACUUMS



- ✓ Accessories included, ideal for cleaning professionals.
- ✓ 100% steel construction.
- ✓ Simultaneous vacuuming of dust, liquids and solids.
- ✓ Liquid level monitored by a floating device to stop when the container is full.
- ✓ Tilting container for easy emptying.

Suction Unit

Power supply	V - Hz	230 - 50 ~ 1
Power	kW	2 x 1,1
Maximum depression	mmH2O	2.400
Maximum air flow rate	m3/h	360
Nozzle	mm	50
Noisiness (EN ISO 3744)	dB(A)	78

Filter Unit

Primary filter		Sack
Surface area - diameter	cm ² -mm	5.000 - 420
Filter media - class	IEC 60335-2-69	Polyester L
Cleaning system		Handbook

Collection unit

Capacity	lt	60
Float		Mechanic
Collection system		Tipping container

Encumbrances

Dimensions	cm	62x60x100h
Weight	kg	32

APPLICATIONS:  General housekeeping  Food, chemical and pharmaceutical industry



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

SUCTION UNIT

Suction is generated by two carbon brush by-pass motors activated by independent switches located on a solid metal head, soundproofed with sound-absorbing material.

FILTER UNIT

The polyester bag filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuumed material is collected in a steel hopper container with an electro-pneumatically controlled swing door for quick discharge.