

# SKY 250 – 500 Oil mist extractors

## AIR FILTRATION SOLUTIONS



- ✓ Reduced energy consumption
- ✓ Quick and easy maintenance.
- ✓ Easy installation on the machine.
- ✓ Quick and easy filter replacement system.

### Suction Unit

Power supply	V - Hz	400 - 50 ~ 3
Power	kW	0,12 - 0,18
Maximum air flow rate	m3/h	250 - 500
Nozzle	mm	100
Construction		Painted Steel
Noisiness (EN ISO 3744)	dB(A)	62

### Filter Unit

Primary filter		Cartridge
Surface area - diameter	cm <sup>2</sup> -mm	2.300/20.000 - 280
Cleaning system		Handbook
Primary filter		Multilayer or Cartridge

### Collection unit

Cyclonic unit		Integrated
---------------	--	------------

### Encumbrances

Dimensions	cm	Ø39 x 47h
Weight	kg	17 - 18

**APPLICATIONS:** Mechanical industry



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

# SKY 250 – 500 Oil mist extractors

## AIR FILTRATION SOLUTIONS

### SUCTION UNIT

The suction unit is a low-power, low-consumption, high airflow blower.

### FILTER UNIT

Versatility of filtration: multi-layer filter (standard) or pleated cartridge with a high filtration surface area and a coalescing pre-filter

### COLLECTION UNIT

Vacuumed and filtered oils and emulsions settle on the wall of the vacuum cleaner and can be recovered through the discharge hose.

### OPTIONALS

- ✓ Kit for air outlet fan
- ✓ Installation kit with riser
- ✓ Installation kit with adjustable riser
- ✓ Wall mounting kit.
- ✓ Adjustable column for floor fixing from 1.5 to 2.5 m.
- ✓ Cyclone pre-filter kit.