

# SILOVAC 100 HV AD

CENTRAL VACUUM SYSTEMS – CENTRAL VACUUM UNITS AND FILTER SILOS



- ✓ Balanced flap discharge system
- ✓ Easy and quick big-bag bagging.
- ✓ Large capacity detachable container. Forklift intakes.

## Suction Unit

Power supply	V - Hz	230 - 50 1~
Power	kW	2 x 1,6
Maximum depression	mmH2O	3600
Maximum air flow rate	m3/h	340
Nozzle	mm	80
Noisiness (EN ISO 3744)	dB(A)	78

## Filter Unit

Surface area - diameter	cm <sup>2</sup> -mm	20.000 - 420
-------------------------	---------------------	--------------

## Collection unit

Capacity	lt	100
----------	----	-----

## Encumbrances

Dimensions	cm	139x126x294h
Weight	kg	160

## APPLICATIONS:



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

# SILOVAC 100 HV AD

CENTRAL VACUUM SYSTEMS – CENTRAL VACUUM UNITS AND FILTER SILOS

## **FILTER UNIT**

---

The filter can be cleaned by means of the integrated mechanical cleaning system: an external filter shaking lever shakes the filter with a vertical movement, ensuring an effective and safe cleaning action, maintaining constant suction power and preventing the dispersion of dust into the environment.

## **COLLECTION UNIT**

---

The material is unloaded directly into big-bags.